



# CERACIMENT BASIC



## CERACIMENT BASIC

Maintenance wax for floors.

**Composite that provides hardness and natural brightness, as well as persistent. Its special formula, allows the enrichment and penetration in the treated floors, especially indicated for Microcemento floors.**

### Properties

- Provides hardness.
- Provides natural and durable brightness.
- Easy to apply.
- Effective at low doses

### Amount needed

By hand 0,25 mL/m<sup>2</sup>

### Technical data

- Nature: Composed of natural waxes and additives.
- Appearance: Opaque liquid.
- Colour: white
- % solids: 2.25
- PH: 6.5-7.5
- Viscosity (Ford cup 4): 10.22 s
- Density: 1,00 ±0.005 g/mL
- Temperature of application: room temperature.

### Application

Add a small dose in water:  
20-25 mL per every 7 litres of water (hand application with sponge, mop)  
25-100 mL per every 10 litres of water (application with machine)

Apply one coat of CERACIMENT on the microcemento surface already sealed, cured and completely clean, using any cleaner Ecoclean or Ecoclean PRO. Keep in mind that the wax treatment is not permanent, it is necessary to repeat the process from time to time.

Important: before applying the wax treatment, wait at least two weeks after applying the varnish Topsealer WT One Coat or Topsealer WT Quick Dry, to ensure its correct curing and thus avoid damaging it.

## Special precautions

---

If the product comes into contact with eyes, wash with plenty of water for 15 minutes. In case of contact with skin, wash with soap and water.

Do not ingest. If swallowed, do not induce vomiting and seek medical assistance immediately.

It is recommended to comply with the following measures:

- Good ventilation.
- Safety glasses.
- Rubber gloves.

Empty containers must be disposed of in accordance with current local regulations.

To prevent the product from drying or thickening, close the lid after each use.

This product is not toxic, dangerous or flammable under normal conditions of handling.

It does not contain any harmful substances that under current regulations call for any additional measures in terms of its labelling.

Keep out of the reach of children.

## Packaging

---

It is available in bottles of 5 litres.

## Cleaning of tools

---

Tools should be cleaned with water and soap immediately after use.

## Storage conditions

---

The product should be stored in its closed original packaging, protected from weather conditions at temperatures between 10°C and 30°C in a dry and well ventilated place, away from direct heat and sunlight. Shelf life is 1 year from the date of production, if stored in well-preserved conditions.



The product should not be used for purposes other than those specified without first having instructions in writing. It is always the user's responsibility to take suitable measures in order to comply with the requirements established in local legislation. Product safety sheets are available for professionals. This technical data sheet will be valid until a new edition appears.

**Last updated:** May 2021