



# PreSealer®



## PRESEALER® Swimming pool sealer / Primer

**Presealer® is a water-based sealer for the Atlanttic system, it creates a protective and protective and consolidating layer.**

**It is also used as a primer for Sttandard, Unlimited, Evolution systems. It consolidates, waterproofs and acts as a bonding bridge between microcement and the varnish.**

**Formulated on the basis of acrylic copolymers in emulsion, stable in humid environment.**

### Properties

- Consolidates microcement coatings.
- Stable in humid environment.
- Resistant to the alkalinity of microcement.
- High adhesion.
- Easy to apply.

### Consumption

- 2 coat: 0.12 l/m<sup>2</sup>

### Technical data

- Water based emulsion
- Milky liquid
- Solids: 18 %.
- PH between 7 and 8.5
- Viscosity 10-11 s (Ford Cup 4)
- Density at 20°C: 1 ± 0,01 g/ml
- Application temperature from 5°C to 35°C (41°F TO 95°F)
- Touch dry 20 minutes

### Application

a. As a swimming pool sealer:

Before applying Presealer® it will be essential to check that the substrate is dry and free of dust. Depending on the climatic conditions and the ventilation of the working area, it is necessary to allow at least 24 hours to elapse before applying the primer on the microcement.

Apply by short nap microfibre roller in two coats, spaced 4 hours apart.

If the sealer is applied and it rains within 7 days, staining of the sealer will occur. It shall be dried, sanded and re-varnished.

b. As a primer for walls and floors:

Before applying Presealer® it is essential to check that the substrate is dry and dust free. Depending on the climatic conditions and the ventilation of the working space, it is necessary to allow at least 24 hours to elapse before applying the primer on the microcement. Apply by short haired microfibre roller in two coats, spaced 4 hours apart.

After applying Presealer®, it is essential to protect the surface with at least two additional coats of one of our with at least two additional coats of one of our Topsealer WT varnishes\* to increase the chemical and abrasion resistance of the coating.

\*Topsealer WT One Coat, Topsealer WT Anti Slip, Topsealer WT Quick Dry, Topsealer WT Spray.

## Special precautions

In case of contact with eyes, rinse with plenty of water for 15 minutes.

In case of contact with skin wash with soap and water.

Do not swallow. If swallowed, do not induce vomiting and seek medical attention immediately.

The following measures are recommended:

- Good ventilation.
- Protective goggles to prevent splashing.
- Rubber gloves.

Empty containers should be disposed of in accordance with the legal regulations in force. To prevent the product from drying out or thickening, close the lid after each use. This product is non-toxic, non-hazardous and non-flammable under normal handling conditions.

This product does not contain any harmful substances that would require, under current regulations, any additional labelling measures. Keep out of reach of children.

For further information see product safety data sheet.

## Packaging

Available in 5 litre containers.

## Cleaning of tools

Tools should be washed with soap and water immediately after use.

## Storage conditions

The product should be stored in its original closed packaging and protected from the weather at temperatures between 10°C and 30°C, in a dry and well-ventilated place, in a dry and well-ventilated place, away from sources of heat and direct sunlight. The shelf life is 1 year from the date of manufacture, if properly stored.



topciment.com

The product should not be used for purposes other than those specified without first having instructions in writing. It is always the user's responsibility to take suitable measures in order to comply with the requirements established in local legislation. Product safety sheets are available for professionals. This technical data sheet will be valid until a new edition appears.

Última edición: June 2021