

ARCOCEM

Bronze Paint



Arcocem Bronze Paint is a water-based metallic paint with fine bronze particles whose application provides a natural bronze effect. Always try the product on a small area prior to the application.

Properties

- Applicable on any surface: microcement, concrete, brick, ceramic, wallboard, plaster, glass, paper and metals.
- High adhesion to the substrate. It is recommended to use first our Primacem Plus, adhesion promoter in non-absorbent areas.
- Apply it with trowel, brush, sponge, roller or spray gun.
- Product ready to use, no dilute with water.

Consumption

Consumption will depend on the surface to be coated and the method of application. If applied with a trowel the consumption level is as follows: 0.15 L/m²

Application

Depending on the desired effect, apply Arcocem Bronze Paint by using one of these two techniques:

- Natural Bronze effect:**
Apply a coat of Arcocem Bronze Paint and, once dry, polish lightly with a 400 sandpaper until the desired brightness is obtained. Finally wipe with a damp cloth in order to remove loose particles and proceed to seal.
- Patina effect:**
Apply two coats of Arcocem Bronze Paint, with 4 hours of separation between them. After 24 hours of the second hand, sanding with grain 120 to expose the bronze particles, and thus facilitate oxidation. For a faster oxidation do not remove the dust. Then apply one coat of Arcocem Oxidizing Agent homogeneously over the entire surface to be treated, do not over-load to prevent pick-up, leave for 2-3 hours and proceed to sealing. In case you want to accentuate the oxide effect, and after 2-3 hour, give a second coat with Arcocem Oxidizing Agent in the desired areas, leaving 2-3 hours before sealing.

Note: Do not apply Arcocem Bronze Paint in outdoors in case of rain forecast.

c. Sealing:

Apply one coat of presealer in order to protect the product and stop the oxidization. After 4 hours, sealing with to coats of Topsealer WT, with an interval of 12 hours between coats.

Special cautions

If the product comes into contact with the eyes, wash immediately with plenty of clean water during 15 minutes. In the event of contact with skin, wash with soap and water. Do not ingest. If swallowed, do not induce vomiting and seek medical attention immediately. It is recommended to comply with the following measures:

- Good air circulation.
- Goggles to prevent splashing.
- Rubber gloves.

Empty containers must be removed according to current legislation. To prevent the product from drying out or thicken, close the lid after each use. This product is not toxic, dangerous neither flammable, under normal handling conditions. This product does not contain any harmful substances which, under current regulation, need any additional measures regarding its labelling.

Keep out of the reach of children.

Packaging

It is available in bottles of 1 litre.

Cleaning of tools

Tools should be cleaned with water and soap immediately after use.

Storage conditions

The product should be stored in its closed original packaging, protected from weather conditions at temperatures between 10°C and 30°C in a dry and well ventilated place, away from direct heat and sunlight. Shelf life is 1 year from the date of production, if stored in well-preserved conditions.



The product should not be used for purposes other than those specified without first having instructions in writing. It is always the user's responsibility to take suitable measures in order to comply with the requirements established in local legislation. Product safety sheets are available for professionals. This technical data sheet will be valid until a new edition appears.

Last updated: June 2017