

ARCOCEM METAL



Arcocem Metal is a range of pigments in aqueous dispersion for applying glazes with metallic reflections in different finishes:

- Arcocem Metal Blanco Plata 500
- Arcocem Metal Aluminio 054
- Arcocem Metal Cobre 063
- Arcocem Metal Cobre Red 063
- Arcocem Metal Gold 063
- Arcocem Metal Bronze 200
- Arcocem Metal Gold 500
- Arcocem Metal Silver 500

Designed to be used as decorative paints. Always check the product on a small area before the application.

Properties

- Applicable over any surface: microcement, concrete, brick, ceramic, wallboard, plaster, glass, paper and metals.
- Apply Arcocem Metal with trowel, sponge or paintbrush.
- Product ready to use, do not dilute in water.

Amount needed

The coverage will depend on the surface to be coated and the application method. In an application with trowel performance level it is as follows:

- Arcocem Metal Silver White 500 – 14,00 m²/l
- Arcocem Metal Aluminium 054 – 12,00 m²/l
- Arcocem Metal Copper 063 – 23,50 m²/l
- Arcocem Metal Copper Red 063 – 23,50 m²/l
- Arcocem Metal Gold 063 – 23,50 m²/l
- Arcocem Metal Bronze 200 – Depends on the type of finish to be obtained.
- Arcocem Metal Gold 500 – Depends on the type of finish to be obtained.
- Arcocem Metal Silver 500 – Depends on the type of finish to be obtained.

If the surface to be coated is in good condition, high performance is obtained, and costs in material and application time are also reduced.

Application

The products come pre-mixed in their different finishes. Before using, homogenize the product. It is convenient to choose the right method for each application. Apply the glaze and let dry for 8 hours, then apply two coats of Presealer, or two coats of presealer and then Topsealer WT, depending on the physical and chemical requirements of the surface to be coated.

Special precautions

If the product comes into contact with the eyes, wash immediately with plenty of clean water during 15 minutes. If contacted with skin rinse with water and soap. Do not ingest. If swallowed, do not induce vomiting and seek medical attention immediately. It is recommended to comply with the following measures:

- Good air circulation.
- Goggles to prevent splashing.
- Rubber gloves.

Empty containers must be removed according to current legislation. To prevent the product from drying out or thicken, close the lid after each use. This product is not toxic, dangerous neither flammable, under normal handling conditions. This product does not contain any harmful substances which, under current regulation, need any additional measures regarding its labelling. Keep out of the reach of children.

Packaging

It is available in packs of 0,5 L.

Cleaning of tools

Tools should be cleaned with water and soap immediately after use.

Storage conditions

The product should be stored in its closed original packaging, protected from weather conditions at temperatures between 10°C and 30°C in a dry and well ventilated place, away from direct heat and sunlight. Shelf life is 1 year from the date of production if stored in well-preserved conditions.



The product should not be used for purposes other than those specified without first having instructions in writing. It is always the user's responsibility to take suitable measures in order to comply with the requirements established in local legislation. Product safety sheets are available for professionals. This technical data sheet will be valid until a new edition appears.

Last updated: June 2018