

CERACIMENT PRO



Maintenance wax for high resistance floors with a metallic finish. Composite that does not yellow over time while preserving the original appearance of the surfaces.

It provides a high degree of brightness and does not affect the conductive characteristics of the treated floors or surfaces. Especially suitable for Microcemento floors.

Properties

- High brightness
- High resistance
- Metallic appearance
- Do not yellow
- Easy to use

Amount needed

Machine 20-40 mL/m²
By hand 30-50 mL/m²

Technical data

- Nature: Metallized emulsion based on acrylic polymers, PE waxes and additives.
- Appearance: Opaque liquid.
- Colour: White
- % solids: 23.37
- PH: 8.5-9.5
- Viscosity (Ford cup 4): 12.84 s
- Density: 1,03 ±0.01 g/mL
- Temperature of application: room temperature.

Application

Use the PURE product, undiluted in water or any other type of solvent. Apply two coats of CERACIMENT PRO on the microcemento surface already sealed, cured and completely clean, using any cleaner Ecoclean or Ecoclean PRO. Keep in mind that the wax treatment is not permanent, it is necessary to repeat the process from time to time.

Important: To ensure its correct curing and thus avoid damaging the surface, wait at least two weeks after applying the varnish Topsealer WT One Coat or Topsealer WT Quick Dry.

Special precautions

If the product comes into contact with eyes, wash with plenty of water for 15 minutes. In case of contact with skin, wash with soap and water.

Do not ingest. If swallowed, do not induce vomiting and seek medical assistance immediately.

It is recommended to comply with the following measures:

- Good ventilation.
- Safety glasses.
- Rubber gloves.

Empty containers must be disposed of in accordance with current local regulations.

To prevent the product from drying or thickening, close the lid after each use.

This product is not toxic, dangerous or flammable under normal conditions of handling. It does not contain any harmful substances that under current regulations call for any additional measures in terms of its labelling.

Keep out of the reach of children.

Packaging

It is available in bottles of 5 litres.

Cleaning of tools

Tools should be cleaned with water and soap immediately after use.

Storage conditions

The product should be stored in its closed original packaging, protected from weather conditions at temperatures between 10°C and 30°C in a dry and well ventilated place, away from direct heat and sunlight. Shelf life is 1 year from the date of production, if stored in well-preserved conditions.



The product should not be used for purposes other than those specified without first having instructions in writing. It is always the user's responsibility to take suitable measures in order to comply with the requirements established in local legislation. Product safety sheets are available for professionals. This technical data sheet will be valid until a new edition appears.

Last updated: June 2017