

ARCOCEM PLUS



Concentrated liquid dye for pigmentation of microcement Topciment.

- Basic chart of 36 colours Topciment.

Properties

- Easily mixable.
- Water- based, no flammable.
- Free from plasticizers, solvents, ammonia and free from emulsifiers.
- High color stability, pigments suitable for outdoor applications.

Application

- To obtain the colours of the catalogue, the dosage indicated on the label must be respected, both for the quantity and for the type of microcement used (Base, Fino, Deck or Stone) and the sealer Tospsealer WT.
- Shake the pigment vigorously until a homogeneous liquid is obtained.
- Pour some kneading liquid into a bucket, add the whole pigment and mix.
- Gradually add the microcemento and the rest of the kneading liquid in the same container until obtaining the viscosity required for each application and a homogeneous colour.

Special precautions

To prevent the product from drying out or thicken, close the lid after each use. This product is not toxic, dangerous or flammable, under normal handling conditions. This product does not contain any harmful substances which, under the current regulation, will take any additional measure as to its labelling.

Packaging

Plastic containers of different sizes depending on the colour and dose.

Storage conditions

The product should be stored in its closed original packaging, protected from weather conditions at temperatures between 10°C and 30°C in a dry and well ventilated place, away from direct heat and sunlight. Shelf life is 1 year from the date of production, if stored in well-preserved conditions.



The product should not be used for purposes other than those specified without first having instructions in writing. It is always the user's responsibility to take suitable measures in order to comply with the requirements established in local legislation. Product safety sheets are available for professionals. This technical data sheet will be valid until a new edition appears.

Last updated: June 2017