



# EMOTTION



## EMOTTION Tile Paint

**EMOTTION is a tile paint designed for the easy renovation of interior spaces.**

**This water-based paint provides extraordinary performance to achieve a high-quality and durable product. Intended as a renewal coating for ceramics, tiles, stoneware, mosaic, etc.**

**It also offers good chemical resistance, making it suitable for use in bathrooms.**

**Available in 11 colors with a satin finish.**

### Characteristics

- Especially recommended for easy renovation.
- Good water resistance.
- Bonds without the need for primers on double-fired and single-fired ceramics, porcelain stoneware, gresite and tiles.
- Ready-to-use product. Remove before use.
- Fast drying.
- Easy application.

### Uses and areas of application

Tile paint for renovation providing a decorative finish.

Ideal for application on porcelain coatings such as stoneware, tiles, mosaic, etc.

### Consumption

In general:

- 0.15 L/m<sup>2</sup> (2 coats)

### Technical data

- Colour: 11 colours available
- Finish: Satin
- Persoz Hardness (s): 150 ± 5
- Density: 1,18 ± 0,02 g/cm<sup>3</sup>
- Cross-cut adhesion (UNE EN ISO 2409): class 1
- Viscosity (H2 at 20 rpm): 3500 ± 1000 mPa•s
- Application temperature above 10°C
- Dry to touch: 30 minutes
- Repainting: 8h
- Drying: 24h
- Curing: 7 days to achieve maximum performance

## Chemical resistances

Application drying time 7 days  
Chemical resistances for contact of 2h

Sample Emottion	
Water	5
Soap	5
Bleach	5
Oil	5
Vinegar	5
Wine	3
Ammonia	5
Alcohol	4

## Characteristics

- Water-based product
- Solids: 43 ± 2%

## Preparation of the substrate

Before painting, the substrate must be properly prepared. It must be dry, clean and free of dust, grease or dirt. For deep cleaning, we recommend using our Ecoclean Basic detergent cleaner.

In case it has been previously varnished or painted, it is necessary to check if it is in good condition and well adhered. If not, it is recommended to remove the previous coating. This can be done by sanding or stripping, ensuring that the surface is in good condition. .If repair is required, consolidation or sealing of joints, proceed prior to the application of Emottion.

In case the original coating is in good condition, a test of compatibility with the substrate can be carried out in an inconspicuous area.

## Application

Before applying EMOTTION, check that the surface is dry and free of grease and dust.

- Remove the product before use.
- Apply with a short nap or microfibre velour roller.
- The application should be carried out at ambient temperatures between 10°C and 30°C.
- Apply one coat and wait for 8 hours before applying the second coat. If the coverage is not correct, apply a third coat.

Allow at least 7 days of drying time before use to achieve its performance.

## Special precautions

For the cleaning and maintenance of surfaces painted with EMOTTION, it is recommended to use neutral soaps and detergents or our Ecoclean Basic diluted 1:10 in water, along with non-abrasive cloths.

Non-flammable product. In case of contact with skin, wash with soap and water. Never use solvents or thinners. Do not swallow. If swallowed, do not induce vomiting and seek medical attention immediately.

The following measures are recommended:

- Good ventilation.
- Use of chemical absorbent mask.
- Protective goggles to prevent splashing.
- Rubber gloves.

Empty containers must be disposed of in accordance with the legal regulations in force.  
To prevent the product from drying out or thickening, close the lid after each use.  
Keep out of the reach of children.

## Packaging

It is available in 2.5 litre packaging.

## Cleaning of tools

Tools should be washed with water immediately after use.

## Storage conditions

The product should be stored in its original closed packaging and protected from the weather at temperatures between 10°C and 30°C in a dry and well-ventilated place, away from sources of heat and direct sunlight. The shelf life is 1 year from the date of manufacture, properly stored.



The product must not be used for purposes other than those specified, without first having the product instruction in its handling. It is always the responsibility of the user to take appropriate measures in order to comply with legal requirements. The Safety Data Sheets of the product are available to the professional.

Last edition: January 2024