



EMOTTION



EMOTTION Tile paint

EMOTTION is a high-performance water-based tile paint for the easy renovation of interior spaces, without the need for prior priming. Ideal for application on porcelain wall tiles such as stoneware, tiles, gresite, etc. It offers good resistance to condensation and is suitable for use in bathrooms. Available in 11 colours with a low satin finish.

Properties

- Especially recommended for the renovation of interior spaces (tiles).
- Good resistance to water and condensation.
- Adheres without prior priming.
- Ready-to-use product, quick-drying and easy to apply.

Performance

- In general:
- 0.15 L/m² (2 layers)

Technical data

PROPERTIES	SPECIFICATION	UNIT	METHOD
Features	Acrylic Resin		
Non-volatile content	52-54	%	UNE-EN ISO 3251:2020
Rotational Viscosity	2500-3500	cp	UNE-EN ISO 2555
Density	1,2±0,1	g/cm ³	UNE-EN ISO 2811-1
Brightness	<12	GU	UNE-EN ISO 2813 (60°)
Adhesion Cutting and Grating	class 1		UNE-EN ISO ISO 2409
Fineness	>7	(Hegman/μ)	UNE-EN ISO 1524
Hardness Persoz	150	s	UNE-EN ISO 1522
Drying time to touch	1	Hours	
Drying time between layers	8	Hours	

Preparation of the support

New surfaces: Before painting, the substrate must be properly prepared. It must be dry, clean and free of dust, grease or dirt. For deep cleaning, we recommend using our Ecoclean Basic detergent cleaner.

Previously painted surfaces: If the surface has been painted or varnished, check whether it is in good condition and well adhered. If not, it is recommended to remove the previous coating. This can be done by sanding or stripping, ensuring that the surface is left in good condition. If joint sealing is required, it is recommended to proceed before Primacem Joint is applied. For its application, consult the technical data sheet of the product.

In case the original coating is in good condition, a preliminary compatibility test with the substrate can be carried out in an inconspicuous area.

Application

Before applying EMOTTION, check that the surface is dry and free of grease and dust.

- Stir the contents until the product is homogenised.
- Apply with a short pile velourex roller or microfibre roller.
- Application should be carried out at ambient temperatures between 10°C and 30°C.
- Apply two to three layers respecting the drying time between layers.
- Allow to dry for at least 7 days before use to achieve its performance.
- After use, cover the container; be careful to leave little air space if it is to be used again for a long period of time.

Maintenance

After 7 days after painting, it can be washed with water and a mild detergent. Do not use abrasive products, scouring pads or brushes that could scratch the surface.

Special precautions

It is essential to follow the instructions on the label of the container. For further information, please refer to the safety data sheet of the product.

Presentation

It comes in 2.5 litre containers.

Cleaning of tools

The tools are washed with water immediately after use.

Storage conditions

The product should be stored in its original closed container and protected from the weather at temperatures between 10°C and 30°C, in a dry and well ventilated place, away from heat sources and direct sunlight. The shelf life is 1 year from date of manufacture, properly stored.



The product must not be used for purposes other than those specified, without first having written instruction in its handling. It is always the responsibility of the user to take appropriate measures in order to comply with legislative requirements. The Safety Data Sheets of the product are available to the professional.

last edition: April 2024