



PreSealer



PRESEALER

Primer

Presealer is a water-based acrylic varnish used as a primer for Standard, Nature and Evolution systems. It consolidates, waterproofs and acts as a bonding bridge between microcement and the varnish.

Formulated on the basis of acrylic copolymers in emulsion, stable in humid environment.

Properties

- Consolidates microcement coatings.
- Stable in humid environment.
- Resistant to the alkalinity of microcement.
- High adhesion.
- Easy to apply

Consumption

2 coats: 0,12 l/m²

Technical data

- Water based emulsion
- Milky liquid
- Solids: 18 %.
- PH between 7 and 8.5
- Viscosity 10-11 s (Ford Cup 4)
- Density at 20°C: 1 ± 0,01 g/ml
- Application temperature from 5°C to 35°C (41°F TO 95°F)
- Touch dry 20 minutes

Application

Before applying PreSealer it is essential to check that the substrate is dry and dust free. Depending on the climatic conditions and the ventilation of the working space, it is necessary to allow at least 24 hours to elapse before applying the primer on the microcement. Apply by short haired microfibre roller in two coats, spaced 4 hours apart.

After applying Presealer, it is essential to protect the surface with at least two additional coats of one of our with at least two additional coats of one of our TopSealer WT varnishes* to increase the chemical and abrasion resistance of the coating.

*TopSealer WT One Coat, TopSealer WT Dragon, TopSealer WT Anti Slip, TopSealer WT Quick Dry, TopSealer WT All in One and TopSealer WT Spray.

Special precautions

In case of contact with eyes, rinse with plenty of water for 15 minutes.
In case of contact with skin wash with soap and water.
Do not swallow. If swallowed, do not induce vomiting and seek medical attention immediately.

The following measures are recommended:

- Good ventilation.
- Protective goggles to prevent splashing.
- Rubber gloves.

Empty containers should be disposed of in accordance with the legal regulations in force. To prevent the product from drying out or thickening, close the lid after each use. This product is non-toxic, non-hazardous and non-flammable under normal handling conditions.

This product does not contain any harmful substances that would require, under current regulations, any additional labelling measures.
Keep out of reach of children.

For further information see product safety data sheet.

Packaging

Available in 5 litre containers.

Cleaning of tools

Tools should be washed with soap and water immediately after use.

Storage conditions

The product must not be used for purposes other than those specified, without first having written instruction in its handling. It is always the responsibility of the user to take appropriate measures in order to comply with the legal requirements. Please refer to The Safety Data Sheets of the product are available to the professional.



The product must not be used for purposes other than those specified, without first having written instruction in its handling. It is always the responsibility of the user to take appropriate measures in order to comply with the legal requirements. Please refer to The Safety Data Sheets of the product are available to the professional.

Last edition: June 2022