



# PRIMACEM®



## PRIMACEM® JOINT Filler putty

**Primacem® Joint is a filling putty for manual application indoors and outdoors. The product is suitable for filling tile joints in kitchens and bathrooms.**

### Properties

- High adhesion on a wide variety of substrates; tiles, ceramics, plaster, plasterboard, concrete, bricks, stone, mortar, painted surfaces, etc.
- Good resistance to water and ambient humidity.
- Retains flexibility after drying.
- Easy to apply and sand

### Technical information

PROPERTIES	SPECIFICATION	UNIT	METHOD
Features	Acrylic Putty		
Colour	White cream		
Non-volatile content	83-85	%	UNE-EN ISO 3251:2020
Density	1,6±0,1	g/cm <sup>3</sup>	UNE-EN ISO 2811-1
Thickness of application	<4		
COV:2004/42/A(c)(40)MaxCOVs	<1	g/L	
Touch time (23°C RH:50%)	5-6	Hours	
Complete drying time	8-10	Hours	
Performance applied on tile joints	0.24	kg/m <sup>2</sup> /mm	

### Substrate preparation and application

- Before applying Primacem® Joint, it is essential to check that the substrate is stable and completely clean.
- Stir contents before use. Application material: spatula or trowel. Maximum application thickness up to 4 mm per coat.
- Depending on the environmental conditions and the ventilation of the working space, it will be necessary to allow 12 - 24 hours to elapse before applying Topcement® microcement.

### Limitations

- Do not apply at temperatures below 10°C or above 35°C, or at humidities above 80%. Do not apply on substrates subject to permanent humidity.
- Do not apply on heated surfaces or in direct sunlight.
- Do not apply on substrates subject to permanent humidity. This product is not suitable for coating surfaces that are to be painted afterwards.

## Special precautions

It is essential to follow the instructions on the label of the container. For further information, please refer to the safety data sheet of the product.  
Empty containers must be disposed of in accordance with current legislation. To prevent the product from drying out or thickening, close the lid after each use.

## Presentation

Available in 1.5 and 3 kg packages

## Cleaning of tools

The tools are washed with water immediately after use.

## Storage conditions

The product should be stored in its original closed container and protected from the weather at temperatures between 10°C and 30°C, in a dry and well ventilated place, away from heat sources and direct sunlight. The shelf life is 1 year from date of manufacture, properly stored.



The product must not be used for purposes other than those specified, without first having written instruction in its handling. It is always the responsibility of the user to take appropriate measures in order to comply with legislative requirements. The Safety Data Sheets of the product are available to the professional.

last edition: March 2025