



PRIMACEM®



PRIMACEM® PLUS

Primer for non-absorbent surfaces

Uses

As a primer based on acrylic copolymers, used as a bonding bridge between non-absorbent surfaces before applying Topciment® microcement.

Properties

- Improves adhesion between non-absorbent substrates such as tiles and microcement.
- Easy to apply, ready-to-use product.
- Water-based product, low VOC (volatile organic compounds), environmentally friendly.

Performance

Its yield is 0.1 L/m².

Technical information

| PROPERTIES | SPECIFICATION | UNIT | METHOD |
|--------------------------------|------------------|-------------------|-------------------------|
| Nature | Acrylic emulsion | | |
| pH | 8-9 | | UNE-EN ISO 19396-1:2020 |
| Density | 1,05±0,05 | g/cm ³ | UNE-EN ISO 2811-1 |
| Non-volatile content | 33-35 | % | UNE-EN ISO 3251:2020 |
| Performance | 8-12 | m ² /L | |
| VOC:2024/42/IIA(h)(30)Max.VOCs | <5 | g/L | |
| Drying time to touch | 30 | minutes | |

Application

The substrates must be clean and free of grease, oils, oxides, paint residues and loose or poorly adhering parts. Apply to the surface by brush or roller. Cover the entire surface, trying to apply a uniform film. The application temperature should be between 5 -30° C. Wait approximately 1 hour before applying Topciment® microcement.

Special precautions

It is essential to follow the instructions on the container label. For further information, please refer to the product safety data sheet. Empty containers must be disposed of in accordance with current legislation.

Presentation

It is available in 1 and 5 L containers.

Cleaning of tools

The tools are washed with water immediately after use.

Storage conditions

The product should be stored in its original closed container and protected from the weather at temperatures between 10°C and 30°C, in a dry and well ventilated place, away from heat sources and direct sunlight. The shelf life is 1 year from date of manufacture, properly stored.



The product must not be used for purposes other than those specified, without first having written instruction in its handling. It is always the responsibility of the user to take appropriate measures in order to comply with legislative requirements. The Safety Data Sheets of the product are available to the professional.

latest edition: January 2025