



PRIMACEM GRIP

Adhesion Promoter with arid



Universal adhesion promoter primer ready for use, for interior and exterior, without emission of volatile organic substances, based on synthetic resins in aqueous dispersion and inert of a siliceous nature.

Properties

- Provides a rough surface ensuring excellent adhesion on smooth or low absorption substrates.
- It is used for the application of micro-cement, plaster, tile placement on concrete supports, ceramic tiles, hydraulic tiles...
- Applicable by roller or brush in one coat.
- The product is supplied ready for use.

Amount needed

0.25 l/m², depending on the porosity of the support.

Technical data

Polymer type: Acrylic
Appearance: Granular milky liquid
PH: Between 7.5 and 9 Apparent density: 1,5 ± 0,05 g / cm³
Dry to the touch: 3/4 h, depending on the applied thickness and weather conditions.

Application



The surface must be dry, clean and firm, free of fats or oils. Shake the container well before using and applying Primacem GRIP to the surface with a brush or roller. Between 15 and 30 minutes, depending on the environmental conditions and the absorption of the support, it can be applied to the plaster, plastering.

Special precautions

If the product comes into contact with eyes, wash with plenty of water for 15 minutes. In case of contact with skin, wash with soap and water.

Do not ingest. If swallowed, do not induce vomiting and seek medical assistance immediately.

It is recommended to comply with the following measures:

- Good ventilation.
- Safety glasses.
- Rubber gloves.

Empty containers must be disposed of in accordance with current local regulations.

To prevent the product from drying or thickening, close the lid after each use.

This product is not toxic, dangerous or flammable under normal conditions of handling. It does not contain any harmful substances that under current regulations call for any additional measures in terms of its labelling.

Keep out of the reach of children.

Packaging

It is available in containers of 5 kg.

Cleaning of tools

Tools should be cleaned with water and soap immediately after use.

Storage conditions

The product should be stored in its closed original packaging, protected from weather conditions at temperatures between 10°C and 30°C in a dry and well ventilated place, away from direct heat and sunlight. Shelf life is 1 year from the date of production, if stored in well-preserved conditions.



The product should not be used for purposes other than those specified without first having instructions in writing. It is always the user's responsibility to take suitable measures in order to comply with the requirements established in local legislation. Product safety sheets are available for professionals. This technical data sheet will be valid until a new edition appears.

Last updated: June 2017