



TopSealer® WT

Topsealer® WT Pool

Water based sealant on lithium base.



Uses

Topsealer® WT Pool is a lithium salt based water-based sealer for the Atlantic system that creates a protective and consolidating film.

Properties

- It offers high durability and improved chemical and wear resistance.
- Resistant to microcement alkalinity
- High adhesion
- Water-based, low VOC (volatile organic compounds), environmentally friendly product
- Easy application.

Technical data

Properties	Specification	Unit	Method
Features	Aqueous solution of Li salts		
Non-volatile content	14-16	%	UNE-EN ISO 3251:2020
Density	1,02±0,05	g/cm ³	UNE-EN ISO 2811-1
pH	10.5-11.5		UNE-EN ISO 19396-1
Drying time to touch (23°C RH:50%)	30-60	min	
Drying time between layers	24	hours	
Performance	10-15	m ² /L	

CHEMICAL RESISTANCES: Immersion method UNE-EN 13529

Legend

- 5: No visible change
- 4: Slight change, only visible with light change
- 3: Moderate visible mark
- 2: Significant mark without affecting surface structure
- 1: Important mark, affects the surface structure

The results obtained are based on an application of 2 layers of varnish 24 hours between layers and after 7 days of application. The contact with the tested chemical agent has been 24 hours, one coat between coats and one coat after 7 days week and one month.

Product	Contact time 24 H	Contact time 1 week	Contact time 1 month
Water	5	5	5
Chlorinated water	5	5	5

Application

Before application, be sure to thoroughly clean the surface. At least 24 hours should elapse before applying the sealer to the microcement. Shake Topsealer pool and apply by spraying at low pressure and spreading evenly by roller or brush to completely cover the substrate, avoiding areas of overspray. Allow each layer to dry for at least 24 hours before applying the next layer. Do not overcoat as this may cause incorrect curing and discolouration.

Avoid leaving traces. Allow to dry, do not add product before it is dry/consolidated. Wait for the pool to be filled at least 7 days after applying Topsealer pool.

The ambient temperature should be between 5 - 30°C, without excessive wind.

The substrate temperature must be between 5 - 25° C.

Special precautions

Topsealer® WT Pool is alkaline and may cause eye and skin irritation. Avoid prolonged contact with skin and eyes and wear suitable protective equipment during application. See product data sheet.

Presentation

It comes in 5-litre carafes.

Cleaning of tools

The tools are washed with water immediately after use

Storage conditions

The product should be stored in its original closed container and protected from the weather at temperatures between 10°C and 30°C, in a dry and well ventilated place, away from sources of heat and direct sunlight. The shelf life is 1 year from the date of manufacture, if stored properly.



The product must not be used for any purpose other than those specified, without first have written instructions on how to handle them. It is always the responsibility user to take the appropriate measures in order to comply with the requirements of the established in the legislation. The professional has at his disposal the Product Safety Data Sheet.

last edition: April 2025