

Properties

- High resistance to alkalis.
- · High colour stability.
- · Compatible with aqueous systems.

Consumption

Depending on the dose colour to be done.

Technical data

BASE	White	Black	Yellow
Density g/mL	2,10	1,56	1,62
Viscosity s (Ford coup 4)	16,53	11,69	12,91

BASE	Green	Red-orange	Blue
Density g/mL	1,91	1,17	1,07
Viscosity s (Ford coup 4)	28,78	11,22	15,53

Application

The product itself, do not mix or dilute with other liquids. Shake vigorously before using.

It is used to get the doses to pigment the microcement according to the colour chart.

Special precautions

To prevent the product from drying out or thicken, close the lid after each use. This product is not toxic, dangerous neither flammable, under normal handling conditions. This product does not contain any harmful substances which, under current regulation, need any additional measures regarding its labelling.

Packaging

It is available in bottles of 0,5 L.

Cleaning of tools

Tools should be cleaned with water and soap immediately after use.

Storage conditions

The product should be stored in its closed original packaging, protected from weather conditions at temperatures between 10°C and 30°C in a dry and well ventilated place, away from direct heat and sunlight. Shelf life is 1 year from the date of production, if stored in well-preserved conditions.





The product should not be used for purposes other than those specified without first having instructions in writing. It is always the user's responsibility to take suitable measures in order to comply with the requirements established in local legislation. Product safety sheets are available for professionals. This technical data sheet will be valid until a new edition appears.

Last updated: June 2018