



CERACIMENT

PRO



CERACIMENT PRO

Maintenance wax for floors

CERACIMENT PRO is a maintenance wax for high resistance floors with a metallic finish. It is a non-yellowing compound that preserves the original appearance of the surfaces.

It provides a high gloss finish and does not affect the conductive characteristics of the treated floors or surfaces. Particularly suitable for microcement floors.

Characteristics

- High gloss
- High resistance
- Metallic appearance
- Non-yellowing
- Easy to use

Consumption

By machine 20 - 40 mL/m²
By hand 30 - 50 mL/m²

Technical data

- Nature: Metallised emulsion based on acrylic polymers, PE waxes and additives.
- Appearance: Opaque liquid
- Colour: White
- % solids: 23 ± 2
- pH: 9 ± 0,5
- Viscosity (Ford 4 cup): 13 ± 1s
- Density: 1,03 ± 0,01 g/mL
- Application temperature: Ambient temperature

Application

Use the product PURE, without dilution with water or any other solvent. Apply two coats of CERACIMENT PRO on the surface of the microcement already sealed, cured and completely clean, using any of the cleaners ECOCLEAN or ECLOCLEAN PRO. It should be taken into account that the waxing treatment is not permanent, it is necessary to repeat the process from time to time, depending on the use of the surface.

Important: before waxing, wait at least two weeks after the application of the Topsealer® WT One Coat, Topsealer® WT or Quick Dry to ensure proper curing and to avoid damage.

Special precautions

In case of contact with eyes, rinse with plenty of water for 15 minutes.
In case of contact with skin wash with soap and water. Do not swallow. If swallowed do not induce vomiting and seek medical attention immediately.

The following measures are recommended:

- Good ventilation
- Protective goggles to prevent splashing.
- Rubber gloves.

Empty containers should be disposed of in accordance with legal regulations.
To prevent the product from drying out or thickening, close the lid after each use.
This product is non-toxic, non-hazardous and non-flammable under normal handling conditions.

This product does not contain any harmful substances that would require, under the current regulations, any additional labelling measures.

Keep out of reach of children.

Packaging

Available in 5-litre containers.

Cleaning of tools

Tools are washed with soap and water immediately after use.

Storage conditions

The product should be stored in its original closed and weatherproof packaging at temperatures between 10°C and 30°C, in a dry and well-ventilated place, away from sources of heat and direct sunlight. The shelf life is 1 year from the date of manufacture, properly stored.



The product must not be used for purposes other than those specified, without first having written instruction in its use. It is always the responsibility of the user to take appropriate measures in order to comply with legal requirements. Safety Data Sheets are available to the professional.

Last edition: June 2021