



topcement.com



# DESMOCEM®



## DESMOCEM® POWDER

Concrete release agent

**DESMOCEM® POWDER is a powdered release agent to improve the removal of moulds used in decorative stamped concrete paving.**

### Properties

- Specially recommended for the removal of moulds for floors and decorative walls made of stamped or concrete.
- To obtain decorative antiquing.

### Preparation

Powdered product, ready to use.

### Performance

Applied to the surface of the stamped concrete:  
100 g/m<sup>2</sup> approx.

### Technical Data

- Colours: Anthracite, White, Cream, Grey, Light Grey, Brown, Walnut, Noir, Pierre, Red, Salmon and Toasted.
- Appearance: Powder
- Density: 0,5 ± 0,1 g/cm<sup>3</sup>
- Water solubility: Insoluble

### Characteristics

- Release powder based on salts of esterified fatty acids and inorganic pigments.
- Insoluble in water.

### Application

Sprinkle DESMOCEM® POWDER directly on the surface to be treated just before placing the mould. Apply some pressure and remove the moulded part from the mould.

Apply manually, at a distance of 30 or 40 cm. apart.

Cover the entire surface, trying to spread it uniformly and avoiding leaving thick layers or areas without covering.

The application must be carried out at room and substrate temperatures between 5°C and 30°C, without excessive wind.

## Special precautions

Non-flammable product. In case of contact with skin wash with soap and water. Never use solvents or thinners. Do not swallow. In case of ingestion do not induce vomiting and seek medical attention immediately.

The following measures are recommended:

- Good ventilation.
- Use of mask with chemical absorbent.
- Protective goggles to prevent splashing.
- Rubber gloves.

Empty containers should be disposed of in accordance with current legislation. To prevent the product from drying out or thickening, close the lid after each use. Keep out of reach of children.

## Packaging

It comes in 10 kg sacks. Also available in buckets.

## Cleaning of tools

The tools are washed with water immediately after use.

## Storage conditions

It should be stored in its original closed packaging and protected from the weather at temperatures between 10°C and 30°C, in a dry and well ventilated place, away from sources of heat and direct sunlight. The shelf life is 1 year from the date of manufacture, if stored properly.



The product must not be used for purposes other than those specified, without first having written instruction in its handling. It is always the responsibility of the user to take appropriate measures in order to comply with legal requirements. The Safety Data Sheets of the product are available to the professional.

Last edition: June 2022