



ECOCLEAN BASIC



Ecoclean Basic

Ecological detergent cleaner

Ecological detergent cleaner, designed with biodegradable and environmentally friendly ingredients. Especially suitable for cleaning persistent dirt.

Its formulation makes it a recommended product for cleaning microcement and other surfaces. Great cleaning and detergent power, which removes the most encrusted dirt, making it ideal for domestic or professional use.

Characteristics

- -Environmentally friendly.
- - Biodegradable.
- - Highly effective on persistent dirt.
- - Slightly alkaline detergent, low foaming, but extraordinary degreasing, descaling and emulsifying power.
- - Removes almost all types of dirt such as grease, food residues, limescale marks, oil, biofilm, etc.
- - For professional and domestic cleaning.
- - In accordance with Regulation (EC) No. 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents.

Uses and areas of application

ECOCLEAN BASIC is specially indicated for the removal of almost any kind of dirt, with a great penetrating power, eliminating encrusted stains.

Especially recommended for cleaning microcement.

For general use, both on walls, floors, equipment and work utensils, etc., and especially on surfaces such as marble, granite, tile, ceramic, stoneware, polished concrete, stainless steel, polished concrete, microcement, plastics, glass-ceramic, etc.

Effectively removes: grease, oils, biofilm, food remains, domestic dirt, limescale residues, etc.

Due to its surfactant and solvent nature, it allows the deep cleaning and removal of grease and dirt, especially on porous surfaces. Highly recommended for cleaning and maintenance in kitchens, bathrooms, floors, dining rooms, etc., as thanks to its cleaning action, it removes the remains of biofilm, food and any other dirt that is generated, contributing to the proper maintenance of the same.

It can be applied from pure to diluted 1:20 in water, depending on the type of surface and

the degree of dirt to be removed. The more concentrated, the faster and more powerful the action.

In homes, offices, shops, waiting rooms, kitchens, bathrooms, canteens, food industry, department stores, warehouses, stores, leisure centres, bars and restaurants, hotels, hospitals, etc.

After its application, the treated surface should be rinsed with water to remove the product residues.

Due to its low foaming power, it can be used with industrial machines such as floor scrubbers. poder de acción.

En viviendas, oficinas, comercios, salas de espera, cocinas, baños, comedores, industria alimentaria, grandes superficies, almacenes, centros de ocio, bares y restaurantes, hoteles, hospitales, etc.

Tras su aplicación, debe aclararse con agua la superficie tratada, para eliminar los restos de producto.

Gracias a su bajo poder espumante, puede emplearse con maquinaria industrial como fregadoras para suelos.

Consumption

Its pure yield is approximately 165-250 ml/m² of product; diluted 1:5 in water 33-50 ml/m²; and diluted 1:20 in water 10-12.5 ml/m², depending on the degree of dirt, the type of substrate and absorption.

Technical data

- Colour: green
- Appearance: clear liquid.
- Density: 1,04 ±0,02 g/cm³
- pH: 9-10
- Diluent: water

Characteristics

- ECOCLEAN BASIC is a concentrated alkaline detergent cleaner based on special alcohols and surfactants, free of EDTA, chlorine, phosphates and ammonia.
-
- Water soluble.

Application

In Microcement:

Use 40-50 mL of product per 5 L of water. Apply with a mop and rinse.
Important: before using ECOCLEAN BASIC, wait at least two weeks from the application of Topsealer WT One Coat or Topsealer WT Quick Dry varnish, to guarantee its correct curing and avoid damaging it.

General uses:

The application is carried out in concentrate and/or dilution with the aid of a synthetic bristle brush, sprayer, sponge, scouring pad or with the aid of suitable cleaning equipment. It can be applied from pure to diluted 1:20 with water, depending on the degree of dirtiness of the surface and the type of substrate.

It is recommended to rub the treated areas with a brush to facilitate the action of the cleaner. Leave to act for 5 to 15 minutes to achieve a deep cleaning. Rinse with water before the product and the dissolved dirt dries. Cleaning with hot water can favour the action of ECOCLEAN BASIC.

For maintenance work, the product can be diluted up to 1:20. It can be used as a floor cleaner for general floor cleaning and maintenance.

On large surfaces, carry out preliminary tests in inconspicuous places until the right dilution is found for each surface and degree of dirtiness, in order to determine the average performance of the product.

Special precautions

- **The following measures are recommended:**
-
- Good ventilation.
- Use of mask with chemical absorbent.
- Protective goggles to avoid splashing.
- Rubber gloves.
- Empty containers should be disposed of in accordance with current legislation.
- To prevent the product from drying out or thickening, close the lid after each use.
- Keep out of reach of children. L17- Irritant product. In case of contact with eyes, rinse with plenty of water for 15 minutes and seek medical advice. In case of contact with skin wash with soap and water. Never use solvents or thinners. Do not swallow. In case of ingestion do not induce vomiting and seek medical attention immediately.
-
- Keep out of reach of children.

Packaging

It is available in 1L and 5 L containers.

Cleaning of tools

The tools are washed with water immediately after use, leaving the product to dry.

Storage conditions

The product should be stored in its original closed container and protected from the weather at temperatures between 10°C and 30°C, in a dry and well-ventilated place, away from heat sources and direct sunlight. The shelf life is 1 year from the date of manufacture, if stored properly.



The product must not be used for purposes other than those specified, without first having written instruction in its handling. It is always the responsibility of the user to take appropriate measures in order to comply with legislative requirements. The Safety Data Sheets of the product are available to the professional.

Last edition: February 2021