



PRIMACEM®



PRIMACEM® GRIP

Aggregate primer for all types of surfaces

Uses

As a primer based on acrylic resins in aqueous dispersion and inerts of siliceous nature, used as a bonding bridge between all types of surfaces and microcement.

Properties

- Provides a roughened surface ensuring excellent adhesion on smooth or low-absorption substrates.
- It is used for the application of all types of surfaces, plastering, laying of tiles on concrete substrates, ceramic, hydraulic tiles...
- Easy to apply, ready-to-use product.
- Water-based product, low VOC (volatile organic compounds), environmentally friendly.

Technical information

PROPERTIES	SPECIFICATION	UNIT	METHOD
Nature	Acrylic emulsion and aggregate		
pH	7,5-9		UNE-EN ISO 19396-1:2020
Density	1,50±0,05	g/cm ³	UNE-EN ISO 2811-1
Viscosity at 23°C Comp. A	5000±1000	mPa·s	EN ISO 3219
Non-volatile content	61-63	%	UNE-EN ISO 3251:2020
Performance	5-3	m ² /Kg	
VOC:2024/42/IIA(g)(30)Max.VOCs	<1	g/L	
Drying time to touch	2-3	hours	

Application

The substrates must be clean and free of grease, oils, oxides, debris and loose or poorly adhering parts. Apply to the surface by brush or roller. Cover the entire surface, trying to apply a uniform film. The application temperature should be between 5 -30° C. Wait approximately 2-3 hours (depending on the environmental conditions and the absorption of the substrate) to apply the Topciment® microcement

Special precautions

It is essential to follow the instructions on the label of the container. For further information, please refer to the product safety data sheet. Empty containers must be disposed of in accordance with current legislation.

Presentation

It comes in 5 kg packages.

Cleaning of tools

The tools are washed with universal solvent immediately after use.

Storage conditions

The product should be stored in its original closed container and protected from the weather at temperatures between 10°C and 30°C, in a dry and well ventilated place, away from heat sources and direct sunlight. The shelf life is 1 year from date of manufacture, properly stored.



The product must not be used for purposes other than those specified, without first having written instruction in its handling. It is always the responsibility of the user to take appropriate measures in order to comply with legislative requirements. The Safety Data Sheets of the product are available to the professional.

last edition: February 2025